

# PIXEL LINX 5P



<Pixel Linx 5P – Local( ), Remote( )>

## Pixel Linx CATx UTP KVM Extender

CAT-5 Twisted Pair Cable  
300m KVM Station

1280 x 1024 (80m ), 1024 x 768 (80m ~ 300m )

5P CPU 1 ,  
4 ( , , , )  
300m

PC, SUN Serial Audio CPU

- CAT-5 Twisted Pair Cable 300m / / (KVM)

- 5P :  
  - > 5 가 1 CPU KVM
  - > First-Come First-Serve KVM
  - > 5 KVM Station

- 300m 1024 x 768 , 80m 1280 x 1024

- 가
- 19" Rack 가

( ) Pixel Linx CATx UTP KVM Extender  
CPU  
CATx Twisted Pair Cable  
300m KVM Station

Pixel Linx 5P CPU 1 ,  
300m 4  
( , , , )  
5 가 Local Remote

PixelLinx 가  
가 가

PIXEL LINX 5P ( PC / SUN Model)		
Video Bandwidth (-3dB)	Local Unit	150MHz
	Remote Unit	300MHz
	UTP Cable 80m	Equalization 95MHz
	1280 x 1024 (80m ) 1024 x 768 (80m ~ 300m )	
	SVGA, VGA, XGA, RGB	
	0.7V P-P	
	3 가	
	DC	
Sync Type	TTL level, HV Separate or Composite, Positive or Negative	
	PC	PC/AT, PS/2
	SUN	Type 5,6 (ex. X3515A)
	PC	Standard PS/2 Two Button, Microsoft IntelliMouse, Logitech 3-Button PS/2
	SUN	Type 5,6 (ex. X3515A)
	Local Unit	CPU
	Remote Unit	DC 9V, Regulated, 1000mA
Connectors	Video to PC	HD15M
	Video to KVM	HD15F
	Keyboard	MiniDin-6 (PC) / MiniDin-8 (SUN)
	Mouse	MiniDIN-6 (PC) / MiniDin-8 (SUN)
	Interconnect	RJ45
/	0 -45 / 5% to 90% RH	
(PC/SUN)	200.0 x 104.07 x 44.40 mm (W X D X H)	
	Local : 552.5g Remote : 568.5g	

# PIXEL LINX 5P

## Application

