

# UltraMatrix 4Xe, 2Xe



## 4User / 2 User KVM Switch

1,000

4 User Station(4xE) ,  
2 User Station(2xE) ,

- 가 PC

PC, Sun, Apple, USB, Workstation,  
ID

가

### Features

- 가
- ID, 가
- 가
- UltraCable 30m
- 1600 x 1280
- AVI(Advanced Visual Interface)
- AVI -
- Inter-Box ,
- 가
- 가

### Applications



### Specifications

Rose Electronics UltraMatrix 4xE 4 (2xE 2  
) , , 가 8 16  
KVM  
(1,000 가 )  
UltraMatrix 4xE 4x8, 4x16, 1x8, 1x16 가  
(2xE 2x4, 2x8, 2x16, 1x8, 1x16),

Visual

UltraMatrix 4xE

가

UltraMatrix 4xE

### Options

UltraCable UltraMatrix  
30m (800x600),  
(800x600)

### UltraMatrix

UltraMatrix 4xE, 2xE 가  
가  
UltraMatrix 4xE 4x8 4x16 4 User가 8  
16 , 1x8 1x16 가  
가 8 16 가  
가  
UltraMatrix 2xE 2x4, 2x8, 2x16 2 User 4, 8,  
16 , 1x8 1x16 가  
가 가  
2 User가 1000 Non-Blocking User(2xE

# UltraMatrix 4Xe, 2Xe

UltraMatrix 가  
UltraCable UltraMatrix  
가

UltraMatrix 가  
KVM ID  
View, Share, Control, Private 가  
가

UltraMatrix  
KVM Switch  
95 / 98 / 2000 / NT, Linux, Sun Solaris / Open Windows,  
Apple, Unix Workstation  
5 , USB  
, Apple

4xE: 42.4 x 12.3 x 8.9cm 2xE: 4/8 - 42.4 x 12.3 x 4.4cm 16 - 42.4 x 12.3 x 8.9cm
4xE 3.6Kg 2Xe 4/8 - 1.8Kg 16 - 3.6Kg
90-240VAC
: IEC320 CPU / KVM : DB25 Female Expansion : HD15Male / Female RS232 : RJ11 6 Conductor
4xE: 1x8 / 2x8 - 250MHz 4x8 / 4x16 - 100MHz 2xE: 1x4 / 1x8 / 2x8 - 250MHz 1x16 / 2x16 - 100MHz
On / Off
0-45 , 5-80% Non-Cond.
UL, cUL, TUV, CE

UltraMatrix AVI(Advanced Visual Interface)  
가



UltraMatrix 가  
가  
6m  
Coax - , ViewLink™ Extender, CrystalView™  
Extender 300m  
19", 23", 24" 가  
가



<UltraMatrix 4xE >