

# VIS-35 Triple-head DVI KVM Extender



VIS-35 Triple-head DVI Fiber Optic KVM Extender

- 1000m Fiber Optic KVM 가
- Thinklogical KVM Extender 가
- 4 Multi-mode Fiber 가 ( )
- USB Tablet, USB , Human Interface Devices(HID) 가
- PS/2, SUN Legacy, USB /
- CPU(KVM Transmitter) , ,
- Duplex Stereo Audio
- 165 MHz VESA Standard가 DVI
- Tablet (DB9)

VIS-35 Fiber Optic Triple-head DVI KVM Extender Triple-Head Video & KVM Application 가

Source Transmitter 3 DVI Receiver

4 Multimode Fiber

Transmitter Receiver

VIS-35 Fiber Optic Triple-head DVI KVM Extender DVI Output 가 Extender 가

Thinklogical Extender Transmitter

VIS Extender Receiver ,

Thinklogical (DVI) (RGB)

VIS-35 KMAS Transmitter Input Receiver Input (USB PS/2, PS/2 SUN ) , VIS-35 , Full Duplex Audio Serial

VIS-35 Digital Fiber Optic Transmitter/ Receiver , KMAS Transmitter

4 Fiber VIS-35 Fiber Optic DVI KVM Receiver . Transmitter Receiver 4 Fiber 3 Fiber 1 Fiber KVMS

1000m KVM Station

1900 x 1200 @ 60 Hz

165 MHz VESA Standard가 DVI

PS/2, SUN, USB

4 Fiber

Transmitter , VIS-35 Receiver KMAS , USB, PS/2, SUN Legacy 가 110-240VAC 가

## Application



<VIS-35 Triple-head DVI KVM Extender Connection Diagram>

## Specification

	DVI : 1900 x 1200 @ 60Hz
	1000m
	100-240VAC, 47-63Hz Universal AC Power Supply
	10watts
	0 ~ 50
	5 ~ 95% RH, Non-condensing
	43.82 x 35.56 x 8.9 cm (W x D x H)
	4.4kg
	EIA 19"
Optical Cable	4 Fiber Multi-Mode 50 Micron ( ) 62.5

# VIS-35 Triple-head DVI KVM Extender

Copper	
DVI Video to Computer	DVI-D to DVI-D Male to Male, 1.8m (3)
USB Keyboard / Mouse to Computer	USB A to B, 1.8m (2)
PS/2 Keyboard / Mouse to Computer	MiniDIN 6, Male to Male, 1.8m (2)
SUN Keyboard / Mouse to Computer	MiniDIN 8, Male to Male, 1.8m (1)
Audio to Computer	3.5mm, Male to Male, 1.8m (2)
Serial to Computer	DB9, Male to Female, 1.8m (1)

Copper Connector	
Video (Transmitter)	DVI-D (3)
Video (Receiver)	DVI-D (3)
Audio MIC	3.5mm Jack (Transmitter Receiver)
Audio MIC	3.5mm Jack (Transmitter Receiver)
Audio Line	3.5mm Jack (Transmitter Receiver)
Serial Port (Transmitter)	DB9 Female
Serial Port(Receiver)	DB9 Male
USB Keyboard/Mouse	USB A (Transmitter Receiver)
USB Local Keyboard /Mouse	USB A (Transmitter)
PS/2 Keyboard/Mouse	MiniDIN 6 Female (Transmitter Receiver)
PS/2 Local Keyboard/Mouse	MiniDIN 6 Female (Transmitter)
SUN Keyboard/Mouse	MiniDIN 8 Female (Transmitter Receiver)
SUN Local Keyboard/Mouse	MiniDIN 8 Female (Transmitter)
USB Keyboard / Mouse from CPU	USB B (Transmitter)
Download USB	USB B (Transmitter Receiver)
Fiber Connector	ST, SC LC

## Ordering Information

VIS-000035-ST	Triple-Head DVI KVM X-tender System Pair, ST
VIS-000035-SC	Triple-Head DVI KVM X-tender System Pair, SC
VIS-000035-LC	Triple-Head DVI KVM X-tender System Pair, LC
VIS-000035-STTX	Triple-Head DVI KVM X-tender System Transmitter, ST
VIS-000035-SCTX	Triple-Head DVI KVM X-tender System Transmitter, SC
VIS-000035-LCTX	Triple-Head DVI KVM X-tender System Transmitter, LC
VIS-000035-STRX	Triple-Head DVI KVM X-tender System Receiver, ST
VIS-000035-SCRX	Triple-Head DVI KVM X-tender System Receiver, SC
VIS-000035-LCRX	Triple-Head DVI KVM X-tender System Receiver, LC