

VIS-4 DVI KVM Extender



1000m KVM Station

1900 x 1200 @ 60 Hz

DVI (Single-Link)

PS/2, SUN, USB

2 Fiber

Application



<VIS-4 DVI KVM Extender Connection Diagram>

Specification

DVI	: 1900 x 1200 @60Hz (DVI Single Link)
Distance	1000m
Power Supply	100-240VAC, 47-63Hz Universal AC Power Supply
Power Consumption	10watts
Humidity	0 ~ 50
Temperature	5 ~ 95% RH, Non-condensing
Dimensions	43.82 x 35.56 x 8.9 cm (W x D x H)
Weight	4.4kg
Form Factor	EIA 19"
Optical Cable	Dual Fiber Multi-Mode 50 Micron () 62.5

Copper	
DVI Video to Computer	DVI-D to DVI-D Male to Male, 1.8m (1)
USB Keyboard / Mouse to Computer	USB A to B, 1.8m (2)
PS/2 Keyboard / Mouse to Computer	MiniDIN 6, Male to Male, 1.8m (2)
SUN Keyboard / Mouse to Computer	MiniDIN 8, Male to Male, 1.8m (1)
Audio to Computer	3.5mm, Male to Male, 1.8m (2)
Serial to Computer	DB9, Male to Female, 1.8m (1)

- 1000m Fiber Optic KVM 가
- Thinklogical KVM Extender
- 2 Multi-mode Fiber 가 ()
- USB Tablet, USB , Human Interface Devices(HID)
- PS/2, SUN Legacy, USB /
- CPU (KVM Transmitter)

- Duplex Stereo Audio
- VESA Standard 가 DVI(Single Link)
- (DB9) Tablet

VIS-4 Fiber Optic KVM Transmitter Source Receiver 2
Multimode Fiber Transmitter Receiver

VIS-4 Fiber Optic KVM Extender DVI KMAS Single Link DVI 가 USB, PS/2, SUN(Legacy) / VIS-4 Transmitter DVI 가

VIS-4 Digital Fiber Optic Transmitter/Receiver USB, Serial, Audio, Stereo Graphics Emitter Transmitter 2

Fiber VIS-4 Fiber Optic DVI KVM Receiver 2 Fiber 1 Fiber 1 KVM


Receiver Transmitter DVI 110-240VAC , USB, PS/2, SUN Legacy 가

VIS-4 DVI KVM Extender

Copper Connector	
Video (Transmitter)	DVI-D (2)
Video (Receiver)	DVI-D (1)
Audio MIC	3.5mm Jack (Transmitter Receiver)
Audio MIC	3.5mm Jack (Transmitter Receiver)
Audio Line	3.5mm Jack (Transmitter Receiver)
Serial Port (Transmitter)	DB9 Female
Serial Port (Receiver)	DB9 Male
USB Keyboard/Mouse	USB A (Transmitter Receiver)
USB Local Keyboard /Mouse	USB A (Transmitter)
PS/2 Keyboard/Mouse	MiniDIN 6 Female (Transmitter Receiver)
PS/2 Local Keyboard/Mouse	MiniDIN 6 Female (Transmitter)
SUN Keyboard/Mouse	MiniDIN 8 Female (Transmitter Receiver)
SUN Local Keyboard/Mouse	MiniDIN 8 Female (Transmitter)
USB Keyboard / Mouse from CPU	USB B (Transmitter)
Download USB	USB B (Transmitter Receiver)
Fiber Connector	ST, SC LC

Ordering Information

VIS-000004-ST	KVM X-tender System Pair, ST
VIS-000004-SC	KVM X-tender System Pair, SC
VIS-000004-LC	KVM X-tender System Pair, LC
VIS-000004-STTX	KVM X-tender System Transmitter, ST
VIS-000004-SCTX	KVM X-tender System Transmitter, SC
VIS-000004-LCTX	KVM X-tender System Transmitter, LC
VIS-000004-STRX	KVM X-tender System Receiver, ST
VIS-000004-SCRX	KVM X-tender System Receiver, SC
VIS-000004-LCRX	KVM X-tender System Receiver, LC



<VIS-4 DVI KVM Extender Transmitter >



<VIS-4 DVI KVM Extender Receiver >